



Product Service

Attestation of Conformity

No. N8A 090762 0063 Rev. 00

Holder of Attestation: **Pylon Technologies Co., Ltd.**

No. 73, Lane 887, Zu Chongzhi Road, Zhangjiang Hi-Tech Park
201203 Pudong, Shanghai
PEOPLE'S REPUBLIC OF CHINA

Product: **Batteries**
(Rechargeable Li-ion Battery)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290223117901

Date, 2023-05-10

(Billy Qiu)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



Product Service

Attestation of Conformity

No. N8A 090762 0063 Rev. 00

Model(s): Force-H2-96/96-V2, Force-H2-96/192-V2, Force-H2-96/288-V2, Force-H2-96/384-V2, Force-H2-96/480-V2

Parameters:

Model:	Force-H2-96/96-V2	Force-H2-96/192-V2	Force-H2-96/288-V2	Force-H2-96/384-V2	Force-H2-96/480-V2
Battery input/output terminal parameters					
Battery type	Li-ion(LFP)				
Rated capacity [Ah]	37				
Rated energy capacity [kWh]	3.55	7.10	10.65	14.20	17.75
Rated voltage [Vd.c.]	96	192	288	384	480
Battery voltage range [Vd.c.]	81~108	162~216	243~324	324~540	405~540
Nominal current [Ad.c.]	7.4				
Maximum charging/discharging current [Ad.c.]	40				
Maximum charging/discharging power [kW]	4.32	8.64	12.96	17.28	21.60
General					
Ambient charging/discharging temperature range(°C)	-10 °C to 55 °C				
Protection class	I				
Ingress protection	IP55				
Operating altitude range [m]	4000				

Tested according to:

EN IEC 62040-1:2019/A11:2021

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

