

12 V 150 Ah (C₁₀₀) Deep Cycle AGM Battery

PHYSICAL CHARACTERISTICS

	SI Units	US Units
Length	513 mm	20.1 inch
Width	189 mm	7.4 inch
Height	223 mm	8.7 inch
Typical weight	40.1 kg	88.42 lbs



Specifications:

- Nominal voltage: 12 V
- Rated capacity: 150 Ah (at C₁₀₀)
- Separator: AGM
- Electrolyte: Sulphuric acid; analytical grade
- Self discharge: < 2.5% per month at 20°C
- Standards: IEC 61056; IEC 61427; IEC 60896
- Venting valve: One way, self resealing
- Degassing system: Central
- Terminal type: Top / Automotive
- Case / lid material: Polypropylene
- Carrying Handles: Available (2)

Performance characteristics:

BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge time	15 min	1 h	5 h	10 h	100 h
End of discharge voltage	9.60 V	9.60 V	10.20 V	10.80 V	10.80 V
Discharge capacity	55 Ah	85 Ah	110 Ah	125 Ah	150 Ah
Constant power discharge (per block)	2450 W	980 W	260 W	150 W	16.5 W
Reserve capacity at 25 A	240 min / 100 Ah				

Temperature correction factor of discharge capacity

Temperature	-20 °C	-10 °C	0 °C	10 °C	20 °C	40 °C
Correction factor	0.50	0.70	0.83	0.91	0.97	1.04

BATTERY CHARGE CONDITIONS

Constant current charge	Current range: 0.1 – 0.2C ₁₀ A
Constant voltage charge	Voltage range: 14.10 – 15.10 V (Recommended: 14.40 V)
Float voltage	13.62 V (2.27 Vpc) at 20 °C
Temperature correction factor	Below 20 °C: + 0.018 V/block/°C; Above 20 °C: - 0.018 V/block/°C
Float application	Recommended: max. 0.1C ₁₀ A / 13.62 V (2.27 Vpc)
Cycle applications	Recommended: max. 0.2C ₁₀ A / 14.40 V (2.40 Vpc) Recharge Ah: at least 105% from previous discharge Ah

