

intAct Bike-Power Classic

Motorcycle batteries | dry pre-charged + acid pack
Maintenance free according to DIN



intAct
Battery-Power

intAct Bike-Power Classic

Motorcycle batteries | dry pre-charged + acid pack
Maintenance free according to DIN

This robust technology, designed to withstand specific impacts associated with motorcycle riding, ensures a long life and reliable starting power in the 12 V range. Regarding acid pack

implementation, all batteries will be delivered with a matching acid pack.

Battery	Japan-Code	Volt	Capacity	Cold cranking amper	Lenght mm	Width mm	Height mm	Position of terminal	Terminal	Degassing
00211	6N2-2A-4	6	2 AH (c20)	10	70	47	96	0		1
00214	6N2A-2C-3*	6	2 AH (c20)	10	70	47	106	1		2
00411	6N4-2A	6	4 AH (c20)	10	71	71	96	1		1
00412	6N4B-2A-3	6	4 AH (c20)	10	100	47	96	1		1
00413	6N4A-4D	6	4 AH (c20)	10	58	62	131	0		1
00414	6N4-2A-7	6	4 AH (c20)	10	71	71	96	1		1
00415	6N4C-1B	6	4 AH (c20)	10	71	71	105	0		3
00611	6N6-3B	6	6 AH (c20)	30	99	57	107	0		5
00613	6N6-1D-2	6	6 AH (c20)	30	99	57	107	0		4
00714	B39-6 (6N7-1)	6	7 AH (c20)	30	126	48	126	0	B	6
00800	6YB8-3B (6YB8L-B)	6	8 AH (c20)	50	120	71	95	0	B	6
00811	B49-6	6	8 AH (c20)	40	91	83	161	1	B	6
01211	6N11A-3A	6	11 AH (c20)	80	122	62	132	0	B	1
01214	6N11A-1B	6	11 AH (c20)	80	122	62	132	0	B	3
01225	6N12A-2D (B54-6A)	6	12 AH (c20)	80	156	57	116	0	B	4
50311	CB2.5L-C	12	2,5 AH (c20)	10	81	71	106	0		2
50312	CB3L-A	12	3 AH (c20)	10	99	57	111	0	B	1
50313	CB3L-B	12	3 AH (c20)	10	99	57	111	0	B	3
50411	CB4L-B	12	4 AH (c20)	20	120	70	92	0	A	3
50411LV	CB 4L-B	12	5 AH (c20)	30	120	70	92	0	A	3
50512	CB5L-B	12	5 AH (c20)	30	121	61	131	0	B	3
50611	12N5.5-3B	12	5,5 AH (c20)	40	138	61	131	0	B	3
50612	12N5.5A-3B	12	5,5 AH (c20)	40	103	90	114	0	B	3
50613	12N5.5-4B	12	5,5 AH (c20)	40	138	61	131	1	B	3
50712	CB7L-B	12	8 AH (c20)	40	137	76	134	0	B	3
50811	CB7C-A	12	8 AH (c20)	50	130	90	114	0	E	4
50813	CB7-A	12	8 AH (c20)	40	137	76	134	1	B	1
50913	CB9A-A	12	9 AH (c20)	50	137	76	155	1	B	1
50914	CB9-B	12	9 AH (c20)	80	137	76	140	1	B	3
50915	CB9L-B	12	9 AH (c20)	80	137	76	140	0	B	3
50916	CB9L-A2	12	9 AH (c20)	80	137	76	140	0	A	1
51111	CB10A-A2	12	11 AH (c20)	90	135	90	155	1	D	1
51112	CB10L-A2	12	11 AH (c20)	90	136	91	146	0	D	1
51113	CB10L-B2	12	11 AH (c20)	90	136	91	146	0	D	3
51211	CB12A-A	12	12 AH (c20)	120	135	81	161	1	B	1
51212	CB12B-B2	12	12 AH (c20)	120	161	91	132	1	D	3
51213	CB12AL-A2	12	12 AH (c20)	120	135	81	161	0	D	1
51215	CB12A-B	12	12 AH (c20)	120	135	81	161	1	B	3
51411	CB14L-A2	12	14 AH (c20)	140	135	91	167	0	D	1
51412	CB14-A2	12	14 AH (c20)	140	135	91	167	1	D	1
51413	CB14L-B2	12	14 AH (c20)	140	135	91	167	0	D	3
51414	CB14-B2	12	14 AH (c20)	140	135	91	167	1	D	3
51615	CB16B-A	12	16 AH (c20)	160	162	92	162	1	C	1
51616	CB16AL-A2	12	16 AH (c20)	120	205	71	164	0	F	1
51617	HCB16A-A (AB)	12	16 AH (c20)	160	151	91	182	1	C	1

Battery	Japan-Code	Volt	Capacity	Cold cranking amper	Lenght mm	Width mm	Height mm	Position of terminal	Terminal	Degassing
51814	51814	12	18 AH (c20)	170	186	81	170	0	G	3
51815	CB18L-A	12	18 AH (c20)	170	182	92	164	0	C	1
51816	CB18-A	12	18 AH (c20)	170	182	92	164	1	C	3
51911	CB16L-B	12	19 AH (c20)	190	176	101	156	0	A	3
51912	CB16-B	12	19 AH (c20)	190	176	101	156	1	B	3
51913	51913	12	19 AH (c20)	170	186	81	170	0	G	1
52012	C50-N18L-A	12	20 AH (c20)	200	206	91	164	0	C	1
52410	12N24-3	12	24 AH (c20)	220	186	125	176	0	G	6
52420	12N24-4	12	24 AH (c20)	220	186	125	176	1	G	6
52430	U1 (9)	12	24 AH (c20)	220	196	131	184	1	B	6
52440	U1R (9)	12	24 AH (c20)	220	196	131	184	0	B	6
52810	CHD4-12 (CHD-12)	12	28 AH (c20)	230	205	130	165	1	I	1
53030*	C60-N30L-A (53030)	12	30 AH (c20)	300	187	130	170	0	G	1
53034*	C60-N30-A (53034)	12	30 AH (c20)	300	187	130	170	1	G	1

* not deliverable with acid pack

Product line: 12 V + 6 V classic types
Model: Motorcycle batteries, maintenance free DIN
Status: Dry pre-charged + acid pack
Quality: OEM quality

Accessories: Connection screws + acid pack
Properties: Good starting performance, durable, safe and reliable
Use: Motor scooters – motorcycles – ATVs/quads – jet skis – ride on lawnmowers – snow mobiles